The `acmart` document class

David M. Jones

30 October 1997
Version 1.6 β

Contents

1 Introduction **1**

2 The docstrip modules **2**

3 The code **2**
3.1 Section headings 7
3.2 Appendices 12
3.3 Lists 14
3.4 Theorems and proofs 18
3.5 Tables of contents 22
3.6 Bibliographies and indexes 23
3.7 Floats and captions 25

4 Bibliography stuff **39**
4.1 Citation macros 40

1 Introduction

This is the `acmart` document class, which is based upon the earlier `acmtrans` document style. Unfortunately, the copy of `acmtrans.sty` I'm working from doesn't contain any attributions, so I can't properly credit the original authors, although the original style seems to have been written by Leslie Lamport, with later modifications by Andrew Appel and Rebecca Davies.

The ACM class has two new options:

preprint for producing a version of the paper suitable for distribution as a preprint (this is the default)

faircopy for producing a version of the paper suitable for submission to the ACM for publication. Currently the only difference is that figures will automatically be put on pages by themselves with appropriate labels at the bottom

of the page. In the future, this may also produce other differences to facilitate copy-editing, such as typesetting the text `\raggedright` instead of fully justified.

2 The docstrip modules

This code uses the following modules:

2e	generate code for LaTeX 2_ε
209	generate code for LaTeX 2.09
cls	generate a document class
trans	generate the `acmtrans` class
bib	generate the `acmbib` package
driver	generate a driver file for the documentation

3 The code

First we output the appropriate header information.

```
1 ⟨*cls⟩
2 ⟨*209⟩
3 % %<*trans>
4 %\typeout{Document Style ‘acmtrans’ \fileversion\space <\filedate>
5 %(dmj).}
6 % %</trans>
7 % %<*!trans>
8 \typeout{Document Style ‘acmart’ \fileversion\space <\filedate>
9 (dmj).}
10 % %</!trans>
11 ⟨/209⟩
12 %
13 ⟨*2e⟩
14 \NeedsTeXFormat{LaTeX2e}
15 % %<*trans>
16 % \ProvidesClass{acmart}[\filedate\space\fileversion\space ACM
17 % transactions class (dmj)]
18 % %</trans>
19 % %<*!trans>
20 \ProvidesClass{acmart}[\filedate\space\fileversion\space ACM
21 article class (dmj)]
22 % %</!trans>
23 ⟨/2e⟩
```

`\@height` `\@width` `\@minus` `\@plus`

Next we add some useful abbreviations from the LaTeX 2_ε kernel to the LaTeX 2.09 version of the document class.

```
24 ⟨*209⟩
25 \def\@height{height}
26 \def\@width{width}
```

```
\def\@minus{minus}
\def\@plus{plus}
\def\hb@xt@{\hbox to}
⟨/209⟩
```

`\if@faircopy`

```
\newif\if@faircopy
\@faircopyfalse
⟨*2e⟩

\DeclareOption{faircopy}{\@faircopytrue}

\DeclareOption{preprint}{\@faircopyfalse}

\DeclareOption{twocolumn}{%
    \PackageWarningNoLine{acmart}{twocolumn mode is not supported}%
}
```

All other options are passed to the article class for processing.

```
\DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}

\ProcessOptions\relax

\LoadClass{article}
⟨/2e⟩
```

`\ds@faircopy`
`\ds@preprint`
`\ds@twocolumn`

```
⟨*209⟩
\def\ds@faircopy{\@faircopytrue}

\def\ds@preprint{\@faircopyfalse}

\def\ds@twocolumn{%
    \typeout{Warning! twocolumn mode is not supported by acmart}%
}

\@twosidetrue
\@mparswitchtrue
\def\ds@draft{\overfullrule 5\p@}
\@options

\lineskip \p@
\normallineskip \p@
\def\baselinestretch{1}
\def\@ptsize{0} %needed for amssymbols.sty
⟨/209⟩
```

`\@normalsize`
`\normalsize`

```
⟨*209⟩
```

```
\def\@normalsize{%
    \@setsize\normalsize{12\p@}\xpt\@xpt
⟨/209⟩
⟨*2e⟩
\renewcommand{\normalsize}{%
    \@setfontsize\normalsize\@xpt\@xiipt
⟨/2e⟩
    \abovedisplayskip 6\p@ \@plus2\p@ \@minus\p@
    \belowdisplayskip \abovedisplayskip
    \abovedisplayshortskip 6\p@ \@minus 3\p@
    \belowdisplayshortskip 6\p@ \@minus 3\p@
    \let\@listi\@listI
}
```

`\small`

```
⟨*209⟩
\def\small{%
    \@setsize\small{11\p@}\ixpt\@ixpt
⟨/209⟩
⟨*2e⟩
\renewcommand{\small}{%
    \@setfontsize\small\@ixpt{11}%
⟨/2e⟩
    \abovedisplayskip 5\p@ \@plus 2\p@ \@minus \p@
    \belowdisplayskip \abovedisplayskip
    \abovedisplayshortskip 5\p@ \@minus 2\p@
    \belowdisplayshortskip 5\p@ \@minus 2\p@
    \def\@listi{%
        \leftmargin\leftmargini
        \topsep 5\p@ \@plus 2\p@ \@minus \p@
        \parsep \z@ \@plus .7\p@
        \itemsep 1.6\p@ \@plus .8\p@
    }%
}
```

`\footnotesize`

```
⟨*209⟩
\def\footnotesize{%
    \@setsize\footnotesize{10pt}\viiipt\@viiipt
⟨/209⟩
⟨*2e⟩
\renewcommand{\footnotesize}{%
    \@setfontsize\footnotesize\@viiipt{9.5}%
⟨/2e⟩
    \abovedisplayskip 4\p@ \@plus \p@
    \belowdisplayskip \abovedisplayskip
    \abovedisplayshortskip 4\p@ \@minus \p@
    \belowdisplayshortskip 4\p@ \@minus \p@
    \def\@listi{%
        \leftmargin\leftmargini
```

```
        \topsep 4\p@ \@plus \p@
        \parsep \z@ \@plus .5\p@
        \itemsep \p@ \@plus .7\p@
    }%
}
```

\scriptsize
\tiny
\large
\Large
\LARGE
\huge
\Huge

```
⟨*209⟩
\def\scriptsize{\@setsize\scriptsize{8\p@}\viipt\@viipt}
\def\tiny{\@setsize\tiny{6\p@}\vpt\@vpt}
\def\large{\@setsize\large{14\p@}\xiipt\@xiipt}
\def\Large{\@setsize\Large{18\p@}\xivpt\@xivpt}
\def\LARGE{\@setsize\LARGE{20\p@}\xviipt\@xviipt}
\def\huge{\@setsize\huge{25\p@}\xxpt\@xxpt}
\def\Huge{\@setsize\Huge{30\p@}\xxvpt\@xxvpt}
⟨/209⟩
⟨*2e⟩
\renewcommand{\scriptsize}{\@setfontsize\scriptsize\@viipt\@viipt}
\renewcommand{\tiny}{\@setfontsize\tiny\@vpt\@vpt}
\renewcommand{\large}{\@setfontsize\large\@xiipt\@xiipt}
\renewcommand{\Large}{\@setfontsize\Large\@xivpt\@xivpt}
\renewcommand{\LARGE}{\@setfontsize\LARGE\@xviipt\@xviipt}
\renewcommand{\huge}{\@setfontsize\huge\@xxpt\@xxpt}
\renewcommand{\Huge}{\@setfontsize\Huge\@xxvpt\@xxvpt}
⟨/2e⟩
```

Added `\rom` for producing upright parens and numerals in italic text. The 2.09 definition of `\rom` is taken from `amsart.sty`, version 1.1b, 31 July 1991. – dmj, 4/19/96

```
⟨*209⟩
\def\rom#1{%
    \leavevmode
    \skip@\lastskip
    \unskip\/%
    \ifdim\skip@=\z@\else\hskip\skip@\fi
    {\rm#1}%
}
⟨/209⟩
⟨2e⟩\let\rom\textup

\normalsize

\oddsidemargin .75in
\evensidemargin .75in
\marginparwidth .5in
\marginparsep .125in
\topmargin .25in
\headheight 12pt
\headsep 16pt
⟨209⟩\footheight 10pt
```

```
\footskip 15pt

\textheight 47pc
\textwidth 30pc
\columnsep 10pt
\columnseprule 0pt

\footnotesep 7pt
\skip\footins 15pt plus 4pt minus 3pt

\floatsep 12pt plus 2pt minus 2pt
\textfloatsep \floatsep

\intextsep 1pc plus 1pc

⟨209⟩\@maxsep 1pc

\dblfloatsep 12pt plus 2pt minus 2pt

\dbltextfloatsep 20pt plus 2pt minus 4pt

⟨209⟩\@dblmaxsep 20pt

\@fptop 0pt plus 1fil

\@fpsep 1pc plus 2fil

\@fpbot 0pt plus 1fil

\@dblfptop 0pt plus 1fil

\@dblfpsep 8pt plus 2fil

\@dblfpbot 0pt plus 1fil

\marginparpush 6pt

\parskip 0pt plus .1pt

% \parindent moved to end

% \parindent 10pt

\partopsep 0pt
```

Set `\clubpenalty` and `\widowpenalty` to their maximum values to inhibit widows and orphans. – dmj, 4/17/96

```
\clubpenalty\@M
\widowpenalty\@M

```

```
⟨*209⟩
\@lowpenalty 51
\@medpenalty 151
\@highpenalty 301

\@beginparpenalty -\@lowpenalty
\@endparpenalty -\@lowpenalty
\@itempenalty -\@lowpenalty
⟨/209⟩
```

3.1 Section headings

```
⟨*209⟩
\newcounter {part}
\newcounter {section}
\newcounter {subsection}[section]
\newcounter {subsubsection}[subsection]
\newcounter {paragraph}[subsubsection]

\def\thepart{\Roman{part}}
\def\thesection{\arabic{section}}
\def\thesubsection{\thesection.\arabic{subsection}}
\def\thesubsubsection{\thesubsection.\arabic{subsubsection}}
\def\theparagraph{\thesubsubsection.\arabic{paragraph}}
⟨/209⟩

\newif\if@uchead
\@ucheadfalse

⟨209⟩\setcounter{secnumdepth}{3}

\def\part{%
    \@startsection{part}{9}{\z@}{-10\p@ \@plus -4\p@ \@minus -2\p@}
        {4\p@}{\normalsize\sf\@ucheadtrue}%
}

\def\section{%
    \@startsection{section}{1}{\z@}{-10\p@ \@plus -4\p@ \@minus -2\p@}%
    {4\p@}{\normalsize\sf\@ucheadtrue}%
}

\def\subsection{%
    \@startsection{subsection}{2}{\z@}{-8\p@ \@plus -2\p@ \@minus -\p@}
```

\c@part
\c@section
\c@subsection
\c@subsubsection
\c@paragraph
\thepart
\thesection
\thesubsection
\thesubsubsection
\theparagraph
\if@uchead
\part
\section
\subsection

```
    {4\p@}{\normalsize\sf}%
}
```

\subsubsection

```
\def\subsubsection{%
    \@startsection{subsubsection}{3}{\parindent}{6\p@ \@plus \p@}%
    {-5\p@}{\normalsize\it}%
}
```

\paragraph

```
\def\paragraph{%
    \@startsection{paragraph}{3}{\parindent}{6\p@ \@plus \p@}%
    {-5\p@}{\normalsize\it}%
}
```

\@period

\subsubsections and \paragraphs are set as run-in headings, with a period added after the heading. However, if the text immediately following the \subsubsection or \paragraph is either another section header or (more likely) a list of some sort, then the period should be ommitted, since the heading will be put on a line by itself. This is implemented in a rather grotty way using \@period and modifying \@startsection, \@xsect, and \@trivlist.

```
\let\@period=.
```

\@startsection

```
\def\@startsection#1#2#3#4#5#6{%
    \if@noskipsec
        \global\let\@period\@empty
        \leavevmode
        \global\let\@period.%
    \fi
    \par
    \@tempskipa #4\relax
    \@afterindenttrue
    \ifdim \@tempskipa <\z@
        \@tempskipa -\@tempskipa
        \@afterindentfalse
    \fi
    \if@nobreak
        \everypar{}%
    \else
        \addpenalty\@secpenalty
        \addvspace\@tempskipa
    \fi
    \@ifstar
        {\@ssect{#3}{#4}{#5}{#6}}
        {\@dblarg{\@sect{#1}{#2}{#3}{#4}{#5}{#6}}}%
}
```

\@sect

```
\def\@sect#1#2#3#4#5#6[#7]#8{%
    \ifnum #2>\c@secnumdepth
        \let\@svsec\@empty
    \else
        \refstepcounter{#1}%
⟨*209⟩
        \edef\@svsec{%
            \begingroup
                \ifnum#2>2 \noexpand\rm \fi
                \csname the#1\endcsname
            \endgroup
            \ifnum #2=1\relax .\fi
            \hskip .5em
        }%
⟨/209⟩
⟨*2e⟩
        \protected@edef\@svsec{%
            \textup{\csname the#1\endcsname}%
            \ifnum #2=1\relax .\fi
            \hskip .5em
        }%
⟨/2e⟩
    \fi
    \@tempskipa #5\relax
    \ifdim \@tempskipa>\z@
        \begingroup
            #6\relax
            \@hangfrom{\hskip #3\relax\@svsec}%
            \begingroup
                \interlinepenalty \@M
```

Unfortunately, we're probably stuck with this. (Or we could redefine `\@M` :-)

It might be worthwhile defining a variant of `\@startsection` that first uppercases the title and then just passes everything along to `\@startsection`. That would make us a little more bullet-proof, since we wouldn't have to worry about tracking future changes in `\@sect`. But it might be more trouble than it's really worth.

```
                \if@uchead
                    \uppercase{#8}%
                \else
                    #8%
                \fi
                \par
            \endgroup
        \endgroup
        \csname #1mark\endcsname{#7}%
        \addcontentsline{toc}{#1}{%
            \ifnum #2>\c@secnumdepth \else
```

```
                \protect\numberline{\csname the#1\endcsname}%
            \fi
            #7%
        }%
    \else
        \def\@svsechd{%
            #6%
            \hskip #3\relax
            \@svsec
            \if@uchead
                \uppercase{#8}%
            \else
                #8%
            \fi
            \csname #1mark\endcsname{#7}%
            \addcontentsline{toc}{#1}{%
                \ifnum #2>\c@secnumdepth \else
                    \protect\numberline{\csname the#1\endcsname}%
                \fi
                #7%
            }%
        }%
    \fi
    \@xsect{#5}%
}
```

\@xsect

```
\def\@xsect#1{%
    \@tempskipa #1\relax
    \ifdim \@tempskipa>\z@
        \par
        \nobreak
        \vskip \@tempskipa
        \@afterheading
    \else
        \global\@nobreakfalse
        \global\@noskipsectrue
        \everypar{%
            \if@noskipsec
                \global\@noskipsecfalse
                \clubpenalty\@M
                \hskip -\parindent
                \begingroup
                    \@svsechd
```

Can't we decide here whether to put the period in? Might have to introduce a new flag, though. How unpleasant.

```
                    \@period
                \endgroup
                \unskip
```

```
                \@tempskipa #1\relax
                \hskip -\@tempskipa
            \else
                \clubpenalty \@clubpenalty
                \everypar{}%
            \fi
        }%
    \fi
    \ignorespaces
}
```

Q. What is `\@period` doing in `\@trivlist`?

A. To handle the case where a `trivlist` is the first item after a `\subsubsection` or `\paragraph`.

Surely there has to be a better way of handling this.

`\@trivlist`

```
\def\@trivlist{%
    \@topsepadd\topsep
    \if@noskipsec
        \global\let\@period\@empty
        \leavevmode
        \global\let\@period.%
    \fi
    \ifvmode
        \advance\@topsepadd\partopsep
    \else
        \unskip
        \par
    \fi
    \if@inlabel
        \@noparitemtrue
        \@noparlisttrue
    \else
        \@noparlistfalse
        \@topsep\@topsepadd
    \fi
    \advance\@topsep \parskip
    \leftskip\z@skip
    \rightskip\@rightskip
    \parfillskip\@flushglue
⟨*2e⟩
    \par@deathcycles\z@
    \@setpar{%
        \if@newlist
            \advance\par@deathcycles\@ne
            \ifnum\par@deathcycles>\@m
                \@noitemerr{\@@par}%
            \fi
        \else
```

```
            {\@@par}%
        \fi
    }%
⟨/2e⟩
⟨209⟩    \@setpar{\if@newlist\else{\@@par}\fi}
    \global\@newlisttrue
    \@outerparskip\parskip
}
```

3.2 Appendices

```
⟨*trans⟩
\newcommand{\apbf}{\small\bf}
%% \newfont{\apbf}{cmbx9}
```

`\@withappendix` Page numbering style for appendices

```
\def\@withappendix#1{\rm A--\number #1}
```

`appenheader`

```
\def\appenheader{%
⟨209⟩    \global\@topnum\z@
⟨209⟩    \global\@botroom \textheight
⟨2e⟩    \suppressfloats[t]%
⟨209⟩    \begin{@float}{figure}[b]
⟨2e⟩    \begin{@float}{figure}[!b]
        \footnotesize
        \newfont{\sc}{cmcsc10}% %%* ACK!
        \parindent\z@
        \null
        \vskip -\textfloatsep
        \vskip 11\p@
        \hrule \@height .2\p@ \@width 30pc
        \vskip 2\p@
        \rule{\z@}{10\p@}%
        \ignorespaces
}

\def\endappenheader{%
    \end{@float}
    \global\let\appendixhead\@empty
}
```

`\appendixhead`

```
\long\def\appendixhead#1#2#3#4{%
    \section*{Appendix}

    An appendix to this paper is available in electronic form
    (PostScript$^{\mbox{\tiny TM}}$).  Any of the following methods
    may be used to obtain it; or see the inside back cover of a
```

```
    current issue for up-to-date instructions.

    \begin{itemize}
    \item By anonymous ftp from {\apbf acm.org}, file
    {\apbf [pubs.journals.#1.append]p#2.ps}
    \item Send electronic mail to {\apbf mailserve@acm.org} containing
    the line\\ {\apbf send~[anonymous.pubs.journals.#1.append]p#2.ps}
    \item By {\it Gopher} from {\apbf acm.org}
    \item By anonymous ftp from {\apbf ftp.cs.princeton.edu},
    file {\apbf pub/#1/append/p#2.ps}
    \item Hardcopy from {\it Article Express}, for a fee: phone
    800-238-3458, fax 201-216-8526, or write P.O.~Box~1801, Hoboken NJ
    07030; and request {\sc acm-#1-appendix-{\small #2}}.
    \end{itemize}

    \clearpage
    \pagenumbering{withappendix}
    \appendix
    \par
    \noindent{\sc this document is the appendix to the following
    paper:}
    \hfill
    \vskip 1em
    \vbox{\sf \parindent\z@\@title}%
    \vskip .5em
    \vbox{\sf \parindent\z@\@author}%
    \vskip .5em\noindent
    \vskip 10\p@\noindent #4
    \vskip 11\p@\noindent
    \hrule \@height .2\p@
    \par
    \begin{bottomstuff}
    \permission
    \copyright #3 ACM
    \par
    \end{bottomstuff}
}
⟨/trans⟩
```

\appendix

```
\def\appendix{%
    \par
    \part{Appendix}%
    \par
    \setcounter{section}{0}%
    \setcounter{subsection}{0}%
    \def\thesection{\Alph{section}}%
    \def\thesubsection{\thesection.\arabic{subsection}}%
}
```

3.3 Lists

```
\labelsep 5pt

\settowidth{\leftmargini}{(9)}
\addtolength\leftmargini\labelsep

\settowidth{\leftmarginii}{(b)}
\addtolength\leftmarginii\labelsep

\leftmarginiii  \leftmarginii
\leftmarginiv   \leftmarginii
\leftmarginv    \leftmarginii
\leftmarginvi   \leftmarginii
\leftmargin     \leftmarginii

\labelwidth\leftmargini
\advance\labelwidth-\labelsep
```

\@listI
\@listi

```
\def\@listI{%
    \leftmargin\leftmargini
    \parsep \z@ \@plus \p@
    \topsep 6\p@ \@plus 2\p@ \@minus 2\p@
    \itemsep 2\p@ \@plus \p@ \@minus .5\p@
}

\let\@listi\@listI

\@listi
```

\@listii

```
\def\@listii{%
    \leftmargin\leftmarginii
    \labelwidth\leftmarginii
    \advance\labelwidth-\labelsep
    \topsep \z@ \@plus \p@
    \parsep \z@ \@plus .5\p@
    \itemsep \parsep
}
```

\@listiii

```
\def\@listiii{%
    \leftmargin\leftmarginiii
    \labelwidth\leftmarginiii
    \advance\labelwidth-\labelsep
    \topsep \z@ \@plus \p@
    \parsep \z@ \@plus .5\p@
    \itemsep \parsep
}
```

\@listiv

```
\def\@listiv{%
    \leftmargin\leftmarginiv
    \labelwidth\leftmarginiv
    \advance\labelwidth-\labelsep
}
```

\@listv

```
\def\@listv{%
    \leftmargin\leftmarginv
    \labelwidth\leftmarginv
    \advance\labelwidth-\labelsep
}
```

\@listvi

```
\def\@listvi{%
    \leftmargin\leftmarginvi
    \labelwidth\leftmarginvi
    \advance\labelwidth-\labelsep
}
```

enumerate

```
\def\enumerate{%
    \ifnum \@enumdepth >3
        \@toodeep
    \else
        \advance\@enumdepth \@ne
        \edef\@enumctr{enum\romannumeral\the\@enumdepth}%
        \list{\csname label\@enumctr\endcsname}{%
            \usecounter{\@enumctr}%
            \def\makelabel##1{##1\hss}%
        }%
    \fi
}

\let\endenumerate\endlist
```

longenum

```
⟨*trans⟩
\def\longenum{%
    \ifnum \@enumdepth >3
        \@toodeep
    \else
        \advance\@enumdepth \@ne
        \edef\@enumctr{enum\romannumeral\the\@enumdepth}%
        \list{\csname label\@enumctr\endcsname}{%
            \usecounter{\@enumctr}%
            \labelwidth\z@
        }%
```

```
    \fi
}
%\leftmargin\z@ \itemindent\parindent}\fi} - this indents each item in
%    enumerate

\let\endlongenum\endlist
⟨/trans⟩
```

Added \rom around all list labels. – dmj, 4/19/96

```
\def\labelenumi{\rom{(\arabic{enumi})}}
\def\theenumi{\arabic{enumi}}
\def\labelenumii{\rom{(\alph{enumii})}}
\def\theenumii{\alph{enumii}}
\def\p@enumii{\rom{\theenumi}}
\def\labelenumiii{\rom{\roman{enumiii}.}}
\def\theenumiii{\roman{enumiii}}
\def\p@enumiii{\rom{\theenumi(\theenumii)}}
\def\labelenumiv{\rom{\Alph{enumiv}.}}
\def\theenumiv{\Alph{enumiv}}
\def\p@enumiv{\rom{\p@enumiii\theenumiii}}
```

itemize

```
\def\itemize{%
    \list{---\hskip -\labelsep}{%
        \settowidth{\leftmargin}{---}%
        \labelwidth\leftmargin
        \addtolength{\labelwidth}{-\labelsep}%
    }%
}

\let\enditemize\endlist
```

longitem

```
⟨*trans⟩
\def\longitem{%
    \list{---}{%
        \labelwidth\z@
        \leftmargin\z@
        \itemindent\parindent
        \advance\itemindent\labelsep
    }%
}

\let\endlongitem\endlist
⟨/trans⟩
```

verse

```
\def\verse{%
    \let\\=\@centercr
```

```
    \list{}{%
        \leftmargin 2pc
        \itemindent -1.5em
        \listparindent \itemindent
        \rightmargin\leftmargin
        \advance\leftmargin 1.5em
    }%
    \item[]
}

\let\endverse\endlist
```

quotation

```
\def\quotation{%
    \list{}{%
        \leftmargin 2pc
        \listparindent .5em
        \itemindent\listparindent
        \rightmargin\leftmargin
        \parsep \z@ \@plus \p@
    }%
    \item[]
}

\let\endquotation=\endlist
```

quote

```
\def\quote{%
    \list{}{%
        \leftmargin 2pc
        \rightmargin\leftmargin
    }%
    \item[]
}

\let\endquote=\endlist
```

description

```
\def\description{%
    \list{}{%
        \listparindent\parindent
        \labelwidth\z@
        \leftmargin\z@
        \itemindent\parindent
        \advance\itemindent\labelsep
        \def\makelabel##1{\it ##1.}%
    }%
}

\let\enddescription\endlist
```

describe

```
\def\describe#1{%
    \list{}{%
        \listparindent\parindent
        \settowidth{\labelwidth}{#1}%
        \leftmargin\labelwidth
        \addtolength\leftmargin\labelsep
        \def\makelabel##1{##1\hfil}%
    }%
}

\let\enddescribe\endlist
```

program There must be a more robust way of doing this. Should really do it by checking we are in a figure, but that would require some added bookkeeping.

```
\def\program{%
⟨209⟩    \ifx\@currsize\normalsize
⟨2e⟩    \ifdim\f@size pt=10pt
        \small
    \else
        \rm
    \fi
    \tabbing
}

\let\endprogram\endtabbing
```

3.4 Theorems and proofs

\@begintheorem

```
\def\@begintheorem#1#2{%
    \trivlist
    \item[%
```

The following two lines seem a little peculiar (repeated 5 times).

```
        \hskip \parindent
        \hskip \labelsep
        {\sc #1\enskip #2.}%
    ]\it
}
```

\@opargbegintheorem

```
\def\@opargbegintheorem#1#2#3{%
    \trivlist
    \item[%
        \hskip \parindent
        \hskip \labelsep
        \begingroup
            \savebox\@tempboxa{\sc #3}%
```

```
            {\sc #1}%
            \enskip #2%
            \ifdim \wd\@tempboxa>\z@
                \enskip
```

Added parentheses around subtitle of lemma. – dmj, 4/19/96

```
                (\box\@tempboxa)%
            \fi.%
        \endgroup
    ]\it
}
```

\if@qeded

```
\newif\if@qeded
\global\@qededfalse
```

proof

```
\def\proof{%
    \global\@qededfalse
    \@ifnextchar[{\@xproof}{\@proof}%
}

\def\endproof{%
    \if@qeded\else\qed\fi
    \endtrivlist
}
```

\@proof

```
\def\@proof{%
    \trivlist
    \item[%
        \hskip \parindent
        \hskip \labelsep
        {\sc Proof.}%
    ]
    \ignorespaces
}
```

\@xproof

```
\def\@xproof[#1]{%
    \trivlist
    \item[\hskip\parindent \hskip\labelsep{\sc Proof #1.}]%
    \ignorespaces
}
```

\qed

```
\def\qed{%
    \unskip
    \kern 10\p@
```

```
    \begingroup
        \unitlength\p@
        \linethickness{.4\p@}%
        \framebox(6,6){}%
    \endgroup
    \global\@qededtrue
}
```

\newdef

```
\def\newdef#1#2{%
    \expandafter\@ifdefinable\csname #1\endcsname
        {\@definecounter{#1}%
         \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}%
         \global\@namedef{#1}{\@defthm{#1}{#2}}%
         \global\@namedef{end#1}{\@endtheorem}%
    }%
}
```

\@defthm

```
\def\@defthm#1#2{%
    \refstepcounter{#1}%
    \@ifnextchar[{\@ydefthm{#1}{#2}}{\@xdefthm{#1}{#2}}%
}
```

\@xdefthm

```
\def\@xdefthm#1#2{%
    \@begindef{#2}{\csname the#1\endcsname}%
    \ignorespaces
}
```

\@ydefthm

```
\def\@ydefthm#1#2[#3]{%
    \trivlist
    \item[%
        \hskip \parindent
        \hskip \labelsep
        \begingroup
            \savebox\@tempboxa{\it #3}%
            {\it #2}%
            \enskip \csname the#1\endcsname
            \ifdim \wd\@tempboxa>\z@
                \enskip
```

The following is inconsistent with the corresponding line in \opargbegintheorem.

```
                \rom(\box\@tempboxa\rom)%
            \fi.%
        \endgroup
    ]%
    \ignorespaces
}
```

\@begindef

```
\def\@begindef#1#2{%
    \trivlist
    \item[%
        \hskip \parskip
        \hskip \labelsep
```

The following is inconsistent with the corresponding line in \opargbegintheorem.

```
        {\it #1\enskip \rom{#2}.}%
    ]%
}
```

\theequation

```
\def\theequation{\arabic{equation}}
```

titlepage

```
\def\titlepage{%
    \@restonecolfalse
    \if@twocolumn
        \@restonecoltrue
        \onecolumn
    \else
        \newpage
    \fi
    \thispagestyle{empty}%
    \c@page\z@
}

\def\endtitlepage{%
    \if@restonecol
        \twocolumn
    \else
        \newpage
    \fi
}

\arraycolsep 2.5pt

⟨*209⟩
\tabcolsep 6pt
\arrayrulewidth .4pt
\doublerulesep 2pt
\tabbingsep \labelsep

\skip\@mpfootins = \skip\footins
\fboxsep = 3pt \fboxrule = .4pt
⟨/209⟩
```

3.5 Tables of contents

\@pnumwidth
\@tocrmarg
\@dotsep
\c@tocdepth

```
808 ⟨*209⟩
809 \def\@pnumwidth{1.55em}
810 \def\@tocrmarg {2.55em}
811 \def\@dotsep{4.5}
812 \setcounter{tocdepth}{3}
```

\tableofcontents

```
813 \def\tableofcontents{%
814     \section*{Contents\@mkboth{CONTENTS}{CONTENTS}}
815     \@starttoc{toc}%
816 }
```

\l@part

```
817 \def\l@part#1#2{%
818     \addpenalty\@secpenalty
819     \addvspace{2.25em \@plus \p@}%
820     \begingroup
821         \@tempdima 3em
822         \parindent \z@
823         \rightskip \@pnumwidth
824         \parfillskip -\@pnumwidth
825         \begingroup
826             \large
827             \bf
828             \leavevmode
829             #1%
830             \hfil
831             \hb@xt@\@pnumwidth{\hss #2}%
832         \endgroup
833         \par
834         \nobreak
835         \endgroup
836 }
```

\l@section

```
837 \def\l@section#1#2{%
838     \addpenalty\@secpenalty
839     \addvspace{1.0em \@plus \p@}%
840     \@tempdima 1.5em
841     \begingroup
842         \parindent \z@
843         \rightskip \@pnumwidth
844         \parfillskip -\@pnumwidth
845         \bf
846         \leavevmode
847         #1%
```

```
        \hfil
        \hb@xt@\@pnumwidth{\hss #2}%
        \par
    \endgroup
}
```

`\l@subsection` `\l@subsubsection`

```
\def\l@subsection{\@dottedtocline{2}{1.5em}{2.3em}}

\def\l@subsubsection{\@dottedtocline{3}{3.8em}{3.2em}}
```

`\listoffigures` `\l@figure`

```
\def\listoffigures{%
    \section*{List of Figures\@mkboth{LIST OF FIGURES}{LIST OF FIGURES}}
    \@starttoc{lof}%
}

\def\l@figure{\@dottedtocline{1}{1.5em}{2.3em}}
```

`\listoftables` `\l@table`

```
\def\listoftables{%
    \section*{List of Tables\@mkboth{LIST OF TABLES}{LIST OF TABLES}}
    \@starttoc{lot}%
}

\let\l@table\l@figure
```

⟨/209⟩

3.6 Bibliographies and indexes

`thebibliography` Which is the correct definition, this one or the one at the end of the file?

```
\def\thebibliography#1{%
    \par
    \footnotesize
    \@startsection{subsection}{2}{\z@}{16\p@ \@plus 2\p@ \@minus \p@}
        {2\p@}{\sf}*{\uppercase{\refname}}
    \list{\arabic{enumi}.}{%
        \settowidth\labelwidth{99.}%
        \leftmargin\labelwidth
        \advance\leftmargin\labelsep
        \topsep \z@
        \parsep \z@ \@plus .1\p@
        \itemsep \parsep
        \usecounter{enumi}%
    }%
    \def\newblock{\hskip .11em \@plus .33em \@minus .07em}%
    \sloppy
    \widowpenalty4500
    \clubpenalty4500
```

```
    \sfcode`\.=1000
    \relax
}

\let\endthebibliography=\endlist
```

`\if@restonecol`

```
⟨*209⟩
\newif\if@restonecol
```

`theindex`

```
\def\theindex{%
    \@restonecoltrue
    \if@twocolumn \@restonecolfalse \fi
    \columnseprule \z@
    \columnsep 35\p@
    \twocolumn[\section*{Index}]
    \@mkboth{INDEX}{INDEX}%
    \thispagestyle{plain}%
    \parindent\z@
    \parskip\z@ \@plus .3\p@\relax
    \let\item\@idxitem
}

\def\endtheindex{%
    \if@restonecol
        \onecolumn
    \else
        \clearpage
    \fi
}
```

`\@idxitem`
`\subitem`

```
\def\@idxitem{\par\hangindent 40\p@}
```

`\subsubitem`

```
\def\subitem{\par\hangindent 40\p@ \hspace*{20\p@}}
```

`\indexspace`

```
\def\subsubitem{\par\hangindent 40\p@ \hspace*{30\p@}}
\def\indexspace{\par \vskip 10\p@ \@plus 5\p@ \@minus 3\p@\relax}
⟨/209⟩
```

`\footnoterule` This is supposed to be of 0 overall height.

Wait a minute. Height .004 points? Surely joking.

```
\def\footnoterule{%
    \kern-3\p@
    \hrule \@width 47\p@ %\@height .004\p@
    \kern 2.6\p@
}
```

3.7 Floats and captions

\@makefntext

```
\long\def\@makefntext#1{%
    \parindent 1em
    \noindent $^{\@thefnmark}$#1%
}
```

\c@topnumber
\topfraction
\c@bottomnumber
\bottomfraction
\c@totalnumber
\textfraction
\floatpagefraction
\c@dbltopnumber
\dbltopfraction
\dblfloatpagefraction

Changed float placement parameters in an attempt to enforce the ACM's styles. In particular, set `bottomnumber` and `\bottomfraction` to 0 to inhibit floats from appearing at the bottom of a page. There should be a minimum of four lines of text on a page, so `\texfraction` should be set to

$$4 \times \left(\frac{\texttt{\baselineskip}}{\texttt{\textheight}} \right) = 4 \times \left(\frac{1\,\mathrm{pc}}{47\,\mathrm{pc}} \right) \approx .085106$$

We'll round this up to .086 since it's probably better to require a little more than we need than to risk allowing less than we want. Finally, we set `\topfraction` to .92 so that floats at the top of a page will be allowed to take up as much as 1 − `\textfraction` of the page. [Note: need to check what value of `\floatpagefraction` should be.] – dmj, 4/17/96

```
⟨209⟩\setcounter{topnumber}{2}
\def\topfraction{.92}
\setcounter{bottomnumber}{0}
\def\bottomfraction{0}
⟨209⟩\setcounter{totalnumber}{3}
\def\textfraction{.086}
\def\floatpagefraction{.6}
⟨209⟩\setcounter{dbltopnumber}{2}
⟨209⟩\def\dbltopfraction{.7}
⟨209⟩\def\dblfloatpagefraction{.5}
```

\@makecaption

Changed colon to period in "long caption" case. [8/14/95–dmj]

We should think about consolidating and/or merging some of the numerous caption macros. For example, `\nocaption` would be unnecessary if `\caption` did something sensible when handed an empty argument. Also, much of `\@makecaption` is identical to code found elsewhere, and should probably be shared.

```
\long\def\@makecaption#1#2{%
    \vskip 1pc
    \setbox\@tempboxa\hbox{#1.\quad #2}%
    \ifdim \wd\@tempboxa >\hsize
        #1.\quad #2\par
    \else
        \centerline{\box\@tempboxa}%
    \fi
}
```

\nocaption

```
\def\nocaption{%
    \refstepcounter\@captype
    \par
    \vskip 1pc
    \centerline{\footnotesize \csname fnum@\@captype \endcsname}%
}
```

\c@figure
\thefigure
\fps@figure
\ftype@figure
\ext@figure
\figurename
\fnum@figure

```
⟨209⟩\newcounter{figure}
\def\thefigure{\@arabic\c@figure}
```

Changed `\fps@figure` from "tbp" to "tp" so that tables will only occur at the top of pages by default. Note that the author can still override this with an explicit optional argument on a figure or table environment, but that case should be taken care of by having `bottomnumber` and `\bottomfraction` both set to 0. Also changed `\fps@table` accordingly. – dmj, 4/17/96

```
\def\fps@figure{tp}
\def\ftype@figure{1}
\def\ext@figure{lof}
\def\figurename{Fig.}
\def\fnum@figure{\figurename~\thefigure}
```

\figfilename
\@figfilename

```
\def\figfilename{\gdef\@figfilename}
\let\@figfilename\@empty
```

figure

If producing fair copy, we force each figure onto a page by itself by (a) forcing a placement specifier of "p" and (b) resizing the figure to be a full page in height.

```
\if@faircopy
⟨209⟩    \newenvironment{figure}{%
⟨2e⟩    \renewenvironment{figure}[1][p]{%
        \let\normalsize\footnotesize
        \normalsize
⟨209⟩        \@ifnextchar[{\@figure}{\@figure[]}%
⟨2e⟩        \@float{figure}[p]%
    }{\end@float
        \global\setbox\@currbox\vbox to\textheight{%
            \vskip\@fptop
            \unvbox\@currbox
            \vskip\@fpbot
```

What to do about figures with no numbers? Should we issue a warning? Should check with ACM to make sure that a caption number is always required.

```
            \noindent \fnum@figure
            \ifx\@figfilename\@empty\else
                : {\tt \@figfilename}%
                \global\let\@figfilename\@empty
            \fi
```

```
        }%
    }
\else
⟨209⟩    \newenvironment{figure}{%
⟨2e⟩    \renewenvironment{figure}{%
        \let\normalsize\footnotesize
        \normalsize
        \@float{figure}
    }{\end@float}
\fi
```

`\@figure`

```
⟨209⟩\def\@figure[#1]{\@float{figure}[p]}
```

`figure*` We don't support twocolumn mode, so `figure*` is identical to `figure`.

```
\expandafter\let\csname figure*\endcsname\figure
\expandafter\let\csname endfigure*\endcsname\endfigure
```

`table`

```
⟨209⟩\newenvironment{table}{%
⟨2e⟩\renewenvironment{table}{%
    \let\normalsize\footnotesize
    \normalsize
    \@float{table}%
}{\end@float}
```

`table*`

```
\expandafter\let\csname table*\endcsname\table
\expandafter\let\csname endtable*\endcsname\endtable
```

`\thetable` See documentation of `\fps@figure`. – dmj, 4/17/96

`\c@table`

```
⟨209⟩\newcounter{table}
```

`\fps@table`

```
\def\thetable{\@Roman\c@table}
```

`\ftype@table`

```
\def\fps@table{tp}
```

`\ext@table`

```
\def\ftype@table{2}
```

`\tablename`

```
\def\ext@table{lot}
```

`\fnum@table`

```
\def\tablename{Table}
\def\fnum@table{\tablename~\thetable}
```

`\@narrowfig`

`\@nfigbox`

```
\newdimen\@narrowfig
```

`\@nfcapbox`

```
\newbox\@nfigbox
```

`\if@nfeven`

```
\newbox\@nfcapbox
\newif\if@nfeven
```

`acmtable`

```
\def\acmtable#1{%
    \@narrowfig #1\relax
    \let\caption\@atcap
```

```
    \let\nocaption\@atnocap
    \@ifnextchar[{\@ntab}{\@ntab[\fps@table]}%
}

\def\@ntab[#1]{%
    \expandafter\table\expandafter[#1]%
    \setbox\@nfigbox\vbox\bgroup
        \hsize \@narrowfig
        \@parboxrestore
}

\def\endacmtable{%
    \hb@xt@\textwidth{%
        \hfil
        \vbox{%
            \hsize \@narrowfig
            \box\@nfcapbox{%
                \baselineskip 4\p@
                \hbox{\vrule \@height .4\p@ \@width \hsize}%
            }%
            \vskip -\p@
            \box\@nfigbox
            \vskip -\p@
            \begingroup
                \baselineskip 4\p@
                \hbox{\vrule \@height .4\p@ \@width \hsize}%
            \endgroup
        }%
        \hfil
    }%
    \end@float
}
```

\@atmakecap

```
\def\@atmakecap#1#2{%
    \setbox\@tempboxa\hbox{#1.\quad #2}%
    \ifdim \wd\@tempboxa >\hsize
        \sloppy #1.\quad #2 \par
    \else
        \centerline{\box\@tempboxa}%
    \fi
}
```

\@atcap

```
\def\@atcap{%
        \par
    \egroup
    \refstepcounter\@captype
    \@dblarg{\@atcapx\@captype}%
}
```

\@atcapx

```
\long\def\@atcapx#1[#2]#3{%
    \addcontentsline{\csname ext@#1\endcsname}{#1}{%
        \protect\numberline{\csname the#1\endcsname}{\ignorespaces #2}%
    }%
    \setbox\@nfcapbox\vbox{%
        \hsize \wd\@nfigbox
        \@parboxrestore
        \@atmakecap{\csname fnum@#1\endcsname}{\ignorespaces #3}%
        \par
    }%
}
```

\@atnocap

```
\def\@atnocap{%
    \egroup
    \refstepcounter\@captype
    \setbox\@nfcapbox\vbox{%
        \hsize \wd\@nfigbox
        \centerline{\footnotesize \fnum@table}
    }%
}
```

narrowfig

\@nfig

```
\def\narrowfig#1{%
    \@narrowfig #1\relax
    \let\caption\@nfcap
    \let\nocaption\@nfnocap
    \@ifnextchar[{\@nfig}{\@nfig[\fps@figure]}%
}

\def\@nfig[#1]{%
    \expandafter\figure\expandafter[#1]%
    \setbox\@nfigbox\vbox\bgroup
        \hsize\@narrowfig
        \@parboxrestore
}

\def\endnarrowfig{%
    \hb@xt@\textwidth{%
        \if@nfeven
            \box\@nfcapbox  \hfil   \box\@nfigbox
        \else
            \box\@nfigbox   \hfil   \box\@nfcapbox
        \fi
    }%
%    \end@float
    \endfigure
}
```

Ah ha! So captions have to go at end of figure, not before. Seems a little unfriendly. Actually, it's necessary for `narrowfig`, but doesn't seem to be necessary for `acmtable`.

\@nfcap

```
\def\@nfcap{%
        \par
    \egroup
    \refstepcounter\@captype
    \@dblarg{\@nfcapx\@captype}%
}
```

\@nfmakecap

```
\def\@nfmakecap #1#2{%
    \setbox\@tempboxa\hbox{#1.\quad #2}%
    \ifdim \wd\@tempboxa >\hsize
        \sloppy #1.\quad #2 \par
    \else
        \@@line{%
            \if@nfeven\else\hfil\fi
            \box\@tempboxa
            \if@nfeven\hfil\fi
        }%
    \fi
}
```

\@nfcapx

```
\long\def\@nfcapx#1[#2]#3{%
    \addcontentsline{\csname ext@#1\endcsname}{#1}{%
        \protect\numberline{\csname the#1\endcsname}{\ignorespaces #2}%
    }%
    \@seteven
    \setbox\@nfcapbox\vbox to \ht\@nfigbox{%
        \hsize \textwidth
        \advance\hsize -2pc
        \advance\hsize -\wd\@nfigbox
        \@parboxrestore
        \vfil
        \@nfmakecap{\csname fnum@#1\endcsname}{\ignorespaces #3}%
        \par
        \vfil
    }%
}
```

\@nfnocap

```
\def\@nfnocap{%
    \egroup
    \refstepcounter\@captype
    \@seteven
```

```
    \setbox\@nfcapbox\vbox to \ht\@nfigbox{%
        \hsize \textwidth
        \advance\hsize -2pc
        \advance\hsize -\wd\@nfigbox
        \@parboxrestore
        \vfil
        \@@line{%
            \if@nfeven\else\hfil\fi
            \footnotesize \fnum@figure
            \if@nfeven\hfil\fi
        }%
        \vfil
    }%
}

\@seteven
  \@nfmsg
\def\@seteven{%
    \@nfeventrue
    \@ifundefined{r@@nf\thefigure}{}{%
        \edef\@tmpnf{\csname r@@nf\thefigure\endcsname}%
        \edef\@tmpnf{\expandafter\@cdr\@tmpnf\@nil}%
        \ifodd\@tmpnf\relax
            \@nfevenfalse
        \fi
    }%
    \label{@nf\thefigure}%
    \edef\@tmpnfx{\if@nfeven e\else o\fi}%
    \edef\@tmpnf{%
        \write\@unused{%
            \noexpand\ifodd \noexpand\c@page
                \noexpand\if \@tmpnfx e%
                    \noexpand\@nfmsg{\thefigure}
                \noexpand\fi
            \noexpand\else
                \noexpand\if \@tmpnfx o%
                    \noexpand\@nfmsg{\thefigure}%
                \noexpand\fi
            \noexpand\fi
        }%
    }%
    \@tmpnf
}

⟨209⟩\def\@nfmsg#1{Bad narrowfig: Figure #1 on page \thepage}
⟨*2e⟩
\def\@nfmsg#1{%
    \PackageWarning{acmart}{Bad narrowfig: Figure #1 on page \thepage}%
}
⟨/2e⟩
```

```
\@narrowfig
  \@nfigbox 1189 \newdimen\@narrowfig
 \@nfcapbox 1190 \newbox\@nfigbox
 \if@nfeven 1191 \newbox\@nfcapbox
            1192 \newif\if@nfeven
```

authinfo Could be redone so that order isn't important. But maybe not worth effort.

```
            1193 \newenvironment{authinfo}{%
            1194     \newcommand{\name}[1] {Name: ##1\newline }
            1195     \newcommand{\address}[1] {Address: ##1\newline }
            1196     \newcommand{\affiliation}[1]  {Affiliation: ##1\newline }
            1197     \newcommand{\biography}[1]  {Biography: ##1\newline}
            1198 }{}
```

sponsor sponsor should be redone as a real environment. But this has to await clarification from ACM about what they want the markup to be.

```
            1199 \newenvironment{sponsor}[2]{%
            1200     Sponsor: #1\strut\newline
            1201     \parbox{3.in}{#2}%
            1202 }{\newline}
```

```
      \and
\maketitle 1203 \def\and{\\ and\\}
            1204
            1205 %* Probably still needs more work
            1206
            1207 \def\maketitle{%
            1208     \newpage
            1209     \thispagestyle{titlepage}%
            1210 ⟨209⟩     \global\@topnum\z@
            1211 ⟨*2e⟩
            1212     \suppressfloats[t]%
            1213 ⟨/2e⟩
            1214 %    \par
            1215     \begingroup
            1216         \lineskip \z@
            1217         \null
            1218         \vskip -30\p@\relax
            1219         \parindent\z@
            1220         \begingroup
            1221             \LARGE
            1222             \raggedright
            1223             \hyphenpenalty\@M
            1224             \sf \@title
            1225             \par
            1226         \endgroup
            1227         \vskip 13.5\p@
            1228 %        \normalsize
            1229 %        \sf
```

```
        %vskip 13.5pt between title and author
        \begingroup
            \addtolength{\baselineskip}{2\p@}%
            \sf
            \@author\par
%            \vskip -2pt
        \endgroup
        \begingroup
            \footnotesize
%            \baselineskip 17pt\relax
            \medskip
%            \hbox{\vrule height .2pt width 30pc}%
            \rule{\textwidth}{.2\p@}%
```

The space around the abstract doesn't look quite right. Should investigate and fix. Maybe change `\parskip` in front matter to get uniform spacing (if that's what's desired).

```
            \ifvoid\@abstract
⟨2e⟩                \PackageWarning{acmart}{an abstract is required}%
⟨*209⟩
                \typeout{^^JPackage acmart Warning: an abstract
                         is required^^J}%
⟨/209⟩
            \else
                \vskip 8.5\p@
                \box\@abstract
            \fi
            \ifx\@categories\@empty \else
                \vskip 4\p@\relax %vskip8.5 space above abstract
⟨209⟩                \def\and{\unskip{\rm;} }%
⟨2e⟩                \def\and{\unskip\textup; }%
                Categories and Subject Descriptors: \@categories\par
            \fi
            \ifx\@terms\@empty\else
                \vskip 4\p@
                General Terms: \ignorespaces
                \@terms
                \par
            \fi
            \ifx\@keywords\@empty\else
                \vskip 4\p@
                Additional Key Words and Phrases: \ignorespaces
                \@keywords
                \par
            \fi
        \endgroup
        \label{@firstpg}%
%        {\baselineskip 14pt\relax
%          \hbox{\vrule height .2pt width 30pc}%
        \rule{\textwidth}{.2\p@}%
```

```
%        }%
        \vskip 23\p@
    \endgroup
    \let\maketitle\relax
```

Now we empty out a few temporary variables. However, note that we don't clear out `\@author` and `\@title`, since we need those later for `\appendixhead`.

```
    \global\let\@categories\@empty
    \global\let\@terms\@empty
    \global\let\@keywords\@empty
}
```

abstract
\@abstract

```
\newbox\@abstract
\def\abstract{%
    \everypar{}%
    \global\setbox\@abstract\vbox\bgroup
        \footnotesize
        \trivlist\item[]\ignorespaces
}

\def\endabstract{%
        \endtrivlist
    \egroup
    \ifx\maketitle\relax
⟨*2e⟩
        \PackageWarning{acmart}{%
            the abstract must be specified before the \MessageBreak
            \string\maketitle\space command%
        }%
⟨/2e⟩
⟨*209⟩
       \typeout{^^JPackage acmart Warning:
            the abstract must be specified before the^^J%
            \string\maketitle\space command^^J%
        }%
⟨/209⟩
        \box\@abstract
    \fi
}
```

\terms
\@terms

```
\def\terms{\gdef\@terms}

\let\@terms\@empty
```

\keywords
\@keywords

```
\def\keywords{\gdef\@keywords}

\let\@keywords\@empty
```

\category
\@category
\@categories

```
\def\category#1#2#3{%
    \@ifnextchar [{\@category{#1}{#2}{#3}}{\@category{#1}{#2}{#3}[]}%
}
```

Should probably issue some sort of warning if the first or second arguments are empty.

```
\def\@category#1#2#3[#4]{%
    \edef\@tempa{\ifx \@categories\@empty \else ; \fi}%
    \begingroup
⟨209⟩        \def\protect{\noexpand\protect\noexpand}%
⟨2e⟩        \let\protect\@unexpandable@protect
        \let\and\relax
        \xdef\@categories{%
            \@categories
            \@tempa
            #1 [{\bf #2}]%
            \if!#4!%
                \if!#3!\else : #3\fi
            \else
                :\space
                \if!#3!\else #3\kern\z@---\hskip\z@\fi
                {\it #4}%
            \fi
        }%
    \endgroup
}

\let\@categories\@empty
```

bottomstuff

```
\def\bottomstuff{%
⟨*209⟩
    \global\@topnum\z@
    \global\@botroom \textheight
    \@float{figure}[b]
⟨/209⟩
⟨*2e⟩
    \enlargethispage{-\baselineskip}%
    \suppressfloats[t]%
    \@float{figure}[!b]
⟨/2e⟩
        \footnotesize
        \parindent\z@
        \null
        \vskip -\textfloatsep
        \vskip 10\p@
        \hrule \@height .2\p@ \@width 30pc
%        \vskip 2\p@
```

Changed this to 4pt to make up for lack of 10pt strut which used to be here in place of the 0pt strut. Could put 10pt strut back in, but then we'd get extra space if there is a blank line after the `\begin{bottomstuff}`.

```
        \vskip 4\p@
```

Took this out since a 0pt rule isn't very useful

```
%        \rule{\z@}{\z@}%
        \ignorespaces
}
```

For LaTeX 2_ε, all we need at the end is `\end@float`. For LaTeX 2.09, we also put in a strut to put in a little extra space at the bottom of the first page.

```
⟨2e⟩\let\endbottomstuff\end@float
⟨*209⟩
\def\endbottomstuff{%
    \par
    \strut
    \end@float
}
⟨/209⟩
```

`\permission` Removed final line ("Permissions may be requested from Publications Dept, ACM Inc., 1515 Broadway, New York, NY 10036 USA, fax +1 (212) 869-0481, or `permissions@acm.org`.") at request of G. Criscione. – 5/12/96

```
\long\def\permission{\par
    Permission to make digital or hard copies of part or all of this
    work for personal or classroom use is granted without fee provided
    that copies are not made or distributed for profit or direct
    commercial advantage and that copies show this notice on the first
    page or initial screen of a display along with the full citation.
    Copyrights for components of this work owned by others than ACM
    must be honored. Abstracting with credit is permitted. To copy
    otherwise, to republish, to post on servers, to redistribute to
    lists, or to use any component of this work in other works,
    requires prior specific permission and/or a fee.
    \par
}
```

`acks` Should this use small-caps instead?

```
\newenvironment{acks}{%
    \@startsection{subsection}{2}{\z@}{-16\p@ \@plus -2\p@ \@minus -\p@}
        {2\p@}{\sf}*{\footnotesize ACKNOWLEDGMENTS}%
}{\par}
```

`received`

```
\newenvironment{received}{%
    \par
    \footnotesize
    \addvspace{18\p@ \@minus 4\p@}%
```

```
    \parindent\z@
}{%
    \label{@lastpg}%
    \par
}

\mark{{}{}}
```

\ps@myheadings

```
\def\ps@myheadings{%
    \let\@mkboth\@gobbletwo
    \def\@oddhead{%
%       \null
        \hfill\small\sf\rightmark
        \hskip 19\p@
        {\Large$\cdot$}%
        \hskip 17\p@
        \thepage
    }%
    \def\@oddfoot{\null\hfill\tiny\@runningfoot}
    \def\@evenhead{%
        \small\sf\thepage
        \hskip 17\p@
        {\Large$\cdot$}%
        \hskip 19\p@
        \leftmark
        \hfill
%       \null
    }%
    \def\@evenfoot{\tiny\@runningfoot \hfill\null}%
    \let\partmark\@gobble
    \let\sectionmark\@gobble
    \let\subsectionmark\@gobble
}
```

\runningfoot
\@runningfoot
\firstfoot
\@firstfoot
\pages

```
\def\runningfoot#1{\def\@runningfoot{#1}}

\let\@runningfoot\@empty

\def\firstfoot#1{\def\@firstfoot{#1}}

\let\@firstfoot\@empty

\def\pages{\pageref{@firstpg}--\pageref{@lastpg}}
```

\ps@titlepage

```
\def\ps@titlepage{%
    \let\@mkboth\@gobbletwo
    \let\@oddhead\@empty
```

```
    \def\@oddfoot{\null\hfill\tiny\@firstfoot}%
    \let\@evenhead\@empty
    \def\@evenfoot{\tiny\@firstfoot\hfill\null}%
}
```

`\today`

```
\def\today{%
    \ifcase\month \or
    January\or
    February\or
    March\or
    April\or
    May\or
    June\or
    July\or
    August\or
    September\or
    October\or
    November\or
    December
    \fi
    \space\number\day, \number\year
}
```

`marray` `marray` is a variant of array where every entry is in `\displaystyle` rather than `\textstyle`

```
\def\marray{%
    \arraycolsep 2.5\p@
    \let\@acol\@arrayacol
    \let\@classz\@marrayclassz
    \let\@classiv\@marrayclassiv
    \let\\\@arraycr
    \let\@halignto\@empty
    \@tabarray
}

\let\endmarray\endarray
```

`\@marrayclassiv` `\@marrayclassz`

```
\def\@marrayclassiv{\@addtopreamble{$\displaystyle \@nextchar$}}

\def\@marrayclassz{%
    \ifcase \@lastchclass
    \@acolampacol
    \or \@ampacol
    \or
    \or
    \or \@addamp
    \or \@acolampacol
```

```
    \or \@firstampfalse \@acol
    \fi
    \edef\@preamble{%
        \@preamble
        \ifcase \@chnum
            \hfil$\relax\displaystyle\@sharp$\hfil
            \or $\relax\displaystyle\@sharp$\hfil
            \or \hfil$\relax\displaystyle\@sharp$%
        \fi
    }%
}

\ps@myheadings

\pagenumbering{arabic}

\onecolumn

%\if@faircopy \raggedright \fi

\parindent 10pt
```
⟨/cls⟩

4 Bibliography stuff

The following code was adapted from version 4 of `chicago.sty` by Glenn Paulley ⟨`gnpaulle@bluebox.uwaterloo.ca`⟩ for the new ACM bibliography style, which is similar (but not identical) to the "Chicago" style. It should be used with the `acmtrans` BibTeX style. The code was originally adapted by Andrew Appel and Rebecca Davies and later reworked by David M. Jones. Most of the prehistory of `chicago.sty` has been removed from the comments below, and the code has been modernized and reorganized somewhat in the interests of efficiency and (hopefully) maintainability.

The `acmtrans` BibTeX style has support for abbreviated author lists and for year-only citations. This is implemented by having the citations actually look like

`\citeauthoryear{`⟨*full-author-info*⟩`}{`⟨*abbrev-author-info*⟩`}{`⟨*year*⟩`}`

These labels are processed by the following LaTeX commands.

`\cite` produces citations with full author list and year, e.g., "[Brown 1978; Jarke, Turner, Stohl, et al. 1985]"

`\citeA` produces citations with only the full author list, e.g., "[Brown; Jarke, Turner and Stohl]"

`\shortcite` produces citations with an abbreviated author list and year.

`\shortciteA` produces only the abbreviated author list.

`\citeyear` produces the year information only, within brackets.

`\citeN` produces citations with the full author list and year, but can be used as nouns in a sentence; parentheses appear only around the year, not around the author names, e.g., "Shneiderman [1978] states that...". If given multiple citekeys, the items referred to should all have the same author; otherwise, an error is signaled.

`\shortciteN` is a variant of `\citeN` that uses an abbreviated author list.

Each of these macros also has a $*$-form, which suppresses the brackets that would normally surround the citation. (For `\citeN` and `\shortciteN`, the $*$-forms are identical to the normal forms.)

Abbreviated author lists use the "et al." construct.

This LaTeX style file must be used a **modern** (1995 or later) version of the `acmtrans` BibTeX style.

```
⟨*bib⟩
⟨cls⟩\typeout{Using ACM bibliography style}
%
⟨*!cls & 2e⟩
\ProvidesPackage{acmbib}{\filedate\space\fileversion\space
ACM bibliography style}
⟨/!cls & 2e⟩
%
⟨!cls & 209⟩\typeout{Package `acmbib' \fileversion\space <\filedate>.}
%
```

4.1 Citation macros

Removed `\def\@citeseppen{-1000}` from beginning of all cite macros, since that was left over from named.sty and not actually used anywhere, although it might not be a bad idea to incorporate something of that sort into our code. – dmj 8/8/95

Each `\cite`-like macro must do three things:

1. Define `\@cite`, which will be used to format the in-text citation. Typically, this must decide whether to put brackets around the reference, and handles the optional argument to `\cite`.

2. Define `\citeauthoryear`, which determinines which part of the citation information is used in the citation.

3. Call the appropriate low-level citation command, which should be essentially identical to the standard LaTeX `\cite` command. In this style, this is either `\@citenormal`, which separates multiple citations by semi-colons, or `\@citeyear`, which uses a comma to separate multiple references. The latter is used whenever the output consists of a series of years.

`\bibyear` See the description of `output.year.check` in `acmtrans.dtx` for an explanation of why this is necessary. The `\unskip`s and `\ignorespaces` are to eliminate any extra space that might creep in otherwise. (The first `\unskip` is the only one that should be necessary, but the others don't hurt.)

```
\newcommand\bibyear[2]{%
    \unskip\quad\ignorespaces#1\unskip
    \if#2..\quad \else \quad#2\relax \fi
}
```

`\bibemph`
`\bibemphic`
`\bibemphsc`

```
⟨*2e⟩
\let\bibemph\emph
\let\bibemphic\emph
\let\bibsc\textsc
⟨/2e⟩
⟨*209⟩
\newcommand{\bibemph}[1]{{\em#1}}
\newcommand{\bibemphic}[1]{{\em#1\/}}
\newcommand{\bibsc}[1]{{\sc#1}}
⟨/209⟩
```

`\@normalcite` `\@normalcite` is used for any citation commands that should surround their output with square brackets.

```
\def\@normalcite{%
    \def\@cite##1##2{[##1\if@tempswa , ##2\fi]}%
}
```

`\@citeNB` `\@citeNB` puts in no brackets at all.

```
\def\@citeNB{%
    \def\@cite##1##2{##1\if@tempswa , ##2\fi}%
}
```

`\@citeRB` `\@citeRB` just produces a right bracket; the left bracket will be supplied by `\citeauthoryear`. This is used by `\citeN` and `\shortciteN`, which only put brackets around the years, not around the authors.

```
\def\@citeRB{%
    \def\@cite##1##2{##1\if@tempswa , ##2\fi]}%
}
```

`\start@cite` Should explain this.

```
\def\start@cite#1#2{%
    \edef\citeauthoryear##1##2##3{%
        ###1%
        \ifnum#2=\z@ \else\ ###2\fi
    }%
    \ifnum#1=\thr@@
        \let\@@cite\@citeyear
    \else
```

```
        \let\@@cite\@citenormal
    \fi
    \@ifstar{\@citeNB\@@cite}{\@normalcite\@@cite}%
}
```

`\cite` This is using the abbreviated author list, rather than the full author list. Is this correct? At any rate, it should be consistent with `\citeNP`.

```
\def\cite{\start@cite13}
```

`\citeNP`

```
\def\citeNP{\cite*}
```

`\citeA`

```
\def\citeA{\start@cite10}
```

`\citeANP`

```
\def\citeANP{\citeA*}
```

`\shortcite`

```
\def\shortcite{\start@cite23}
```

`\shortciteNP`

```
\def\shortciteNP{\shortcite*}
```

`\shortciteA`

```
\def\shortciteA{\start@cite20}
```

`\shortciteANP`

```
\def\shortciteANP{\shortciteA*}
```

`\citeyear`

```
\def\citeyear{\start@cite30}
```

`\citeyearNP`

```
\def\citeyearNP{\citeyear*}
```

`\citeN`

```
\def\citeN{%
    \@citeRB
    \def\citeauthoryear##1##2##3{##1\ [##3%
        \def\reserved@a{##1}%
        \def\citeauthoryear####1####2####3{%
            \def\reserved@b{####1}%
            \ifx\reserved@a\reserved@b
                ####3%
            \else
⟨*2e⟩
                \PackageError{acmart}{author mismatch in \string\citeN}%
```

```
⟨/2e⟩
⟨*209⟩
                \errmessage{Package acmart Error: author mismatch
                          in \string\citeN^^J^^J%
                      See the acmart package documentation for explanation}%
⟨/209⟩
            \fi
        }%
    }%
    \@ifstar\@citeyear\@citeyear
}
```

`\shortciteN`

```
\def\shortciteN{%
    \@citeRB
    \def\citeauthoryear##1##2##3{##2\ [##3%
```

Should `\shortciteN` compare the full author lists or the abbreviated author lists (as it currently does)?

```
        \def\reserved@a{##2}%
        \def\citeauthoryear####1####2####3{%
            \def\reserved@b{####2}%
            \ifx\reserved@a\reserved@b
                ####3%
            \else
⟨*2e⟩
                \PackageError{acmart}{%
                    author mismatch in \string\shortciteN
                }%
⟨/2e⟩
⟨*209⟩
                \errmessage{Package acmart Error: author mismatch
                          in \string\shortciteN^^J^^J%
                      See the acmart package documentation for explanation}%
⟨/209⟩
            \fi
        }%
    }%
    \@ifstar\@citeyear\@citeyear
}
```

`\@citenormal` `\@citeyear`

```
\def\@citenormal{%
    \@ifnextchar [{\@tempswatrue\@citex;}
                  {\@tempswafalse\@citex;[]}%
}
%
\def\@citeyear{%
    \@ifnextchar [{\@tempswatrue\@citex,}%
                  {\@tempswafalse\@citex,[]}%
```

```
}
```

`\@citex` Although multiple citations within a single cite command should normally be separated by semi-colons, there are times when commas should be used instead. So, we modify the `\@citex` macro to take the delimiter as a parameter.

```
\def\@citex#1[#2]#3{%
    \let\@citea\@empty
    \@cite{%
        \@for\@citeb:=#3\do{%
            \@citea
            \def\@citea{#1 }%
            \edef\@citeb{\expandafter\@iden\@citeb}%
            \if@filesw
                \immediate\write\@auxout{\string\citation{\@citeb}}%
            \fi
            \@ifundefined{b@\@citeb}{%
⟨2e⟩                {\reset@font\bfseries ?}%
⟨209⟩                {\bf ?}%
⟨2e⟩                \G@refundefinedtrue
⟨2e⟩                \@latex@warning{%
⟨209⟩                 \@warning{%
                     Citation `\@citeb' on page \thepage\space undefined%
                }%
            }%
            {\csname b@\@citeb\endcsname}%
        }%
    }{#2}%
}
```

`\@biblabel` (from apalike.sty) No labels in the bibliography.

```
\let\@biblabel\@gobble
⟨/bib⟩
```

`\bibindent` Indent second and subsequent lines of bibliographic entries. Stolen from openbib.sty: `\newblock` is set to `\@empty`. (???)

```
⟨*cls⟩
\newdimen\bibindent
\bibindent=1.5em
```

`\refname`

```
⟨209⟩\def\refname{References}
```

`thebibliography` Which is the correct definition of `thebibliography`, this one or the earlier one?

```
\def\thebibliography#1{%
    \footnotesize
    \section*{%
        \refname
        \@mkboth{\uppercase{\refname}}{\uppercase{\refname}}%
    }%
```

```
    \list{[\arabic{enumi}]}{%
        \settowidth\labelwidth{[#1]}%
        \leftmargin\labelwidth
        \advance\leftmargin\labelsep
        \advance\leftmargin\bibindent
        \itemindent -\bibindent
        \listparindent \itemindent
        \parsep \z@
        \usecounter{enumi}%
    }%
    \let\newblock\@empty
    \sloppy
    \sfcode`\.=1000\relax
}
```
⟨/cls⟩

Index

Numbers written in italic refer to the page where the corresponding entry is described, the ones underlined to the code line of the definition, the rest to the code lines where the entry is used.

Symbols

\@@cite 1538, 1540, 1542
\@@line 1115, 1148
\@@par 398, 401, 405
\@Roman 1001
\@abstract 1243, 1251, 1284, 1287, 1308
\@acol 1459, 1478
\@acolampacol 1472, 1477
\@addamp 1476
\@addtopreamble . . 1468
\@afterheading 344
\@afterindentfalse . 260
\@afterindenttrue . 257
\@ampacol 1473
\@arrayacol 1459
\@arraycr 1462
\@atcap 1013, 1054
\@atcapx . . . 1058, 1060
\@atmakecap . 1046, 1067
\@atnocap . . 1014, 1071
\@author 466, 1234
\@auxout 1617
\@begindef . . . 749, 769
\@beginparpenalty . 208
\@begintheorem 677
\@biblabel 1632
\@botroom . . . 415, 1345
\@captype 948, 951, 1057, 1058, 1073, 1107, 1108, 1140
\@categories . . 1253, 1257, 1280, 1317
\@category 1317
\@cdr 1160
\@chnum 1482
\@citeNB . . . 1526, 1542
\@citeRB 1529, 1555, 1577
\@citea 1610, 1613, 1614
\@citeb 1612, 1615, 1617, 1619, 1625, 1628
\@citenormal 1540, 1600
\@citex . 1601, 1602, 1606, 1607, 1609
\@citeyear . . . 1538, 1574, 1598, 1600
\@classiv 1461
\@classz 1460
\@clubpenalty 361
\@currbox 970, 972
\@currsize 667
\@dblarg 270, 1058, 1108
\@dblfpbot 189
\@dblfpsep 187
\@dblfptop 185
\@dblmaxsep 177
\@definecounter . . . 738
\@defthm 740, 744
\@dotsep 808
\@dottedtocline 853, 855, 861
\@endparpenalty . . . 209
\@endtheorem 741
\@enumctr 550–552, 565–567
\@enumdepth 546, 549, 550, 561, 564, 565
\@evenfoot . 1419, 1438
\@evenhead . 1410, 1437
\@faircopyfalse 32, 37, 51
\@faircopytrue . . 35, 49
\@figfilename 960, 975–977
\@figure 967, 989
\@firstampfalse . . 1478

\@firstfoot 1424, 1436, 1438
\@flushglue 391
\@for 1612
\@fpbot 183, 973
\@fpsep 181
\@fptop 179, 971
\@halignto 1463
\@hangfrom 299
\@height 24, 425, 470, 921, 1032, 1039, 1358
\@highpenalty 206
\@iden 1615
\@idxitem 904, 914
\@ifdefinable 737
\@ifnextchar 705, 746, 967, 1015, 1083, 1318, 1601, 1606
\@ifstar 268, 1542, 1574, 1598
\@ifundefined 1158, 1619
\@itempenalty 210
\@keywords . . . 1265, 1268, 1282, 1314
\@lastchclass 1471
\@latex@warning . . 1623
\@listI 78, 504
\@listi . 78, 92, 111, 504
\@listii 514
\@listiii 522
\@listiv 530
\@listv 535
\@listvi 540
\@lowpenalty 204, 208–210
\@makecaption 938
\@makefntext 924
\@marrayclassiv 1461, 1468
\@marrayclassz 1460, 1468
\@maxsep 171
\@medpenalty 205
\@minus 24
\@mparswitchtrue . . 57
\@mpfootins 805
\@namedef 740, 741
\@narrowfig 1007, 1012, 1021, 1029, 1080, 1089, 1189
\@newlisttrue 406
\@nextchar 1468
\@nfcap 1081, 1104
\@nfcapbox 1007, 1030, 1064, 1074, 1096, 1098, 1127, 1142, 1189
\@nfcapx . . . 1108, 1122
\@nfevenfalse 1162
\@nfeventrue 1157
\@nfig 1079
\@nfigbox 1007, 1020, 1035, 1065, 1075, 1088, 1096, 1098, 1127, 1130, 1142, 1145, 1189
\@nfmakecap . 1110, 1133
\@nfmsg 1156
\@nfnocap . . 1082, 1138
\@nobreakfalse 346
\@noitemerr 398
\@noparitemtrue . . . 382
\@noparlistfalse . . 385
\@noparlisttrue . . . 383
\@normalcite 1523, 1542
\@normalsize 66
\@noskipsecfalse . . 350
\@noskipsectrue . . . 347
\@ntab 1015, 1018
\@oddfoot . . 1409, 1436
\@oddhead . . 1401, 1435
\@opargbegintheorem 685
\@options 59
\@outerparskip 407
\@parboxrestore 1022, 1066, 1090, 1131, 1146
\@period . . 248, 251, 253, 355, 371, 373
\@plus 24
\@pnumwidth 808, 823, 824, 831, 843, 844, 849
\@preamble . 1480, 1481
\@proof 705, 712
\@ptsize 64
\@qededfalse . . 702, 704
\@qededtrue 734
\@restonecolfalse 779, 896
\@restonecoltrue 781, 895
\@rightskip 390
\@runningfoot 1409, 1419, 1424
\@secpenalty 265, 818, 838
\@sect 270, 272
\@seteven 1126, 1141, 1156
\@setfontsize . . 72, 86, 105, 128–134
\@setpar 394, 405
\@setsize 68, 82, 101, 119–125
\@sharp 1483–1485
\@ssect 269
\@startsection 229, 233, 237, 241, 245, 249, 872, 1386
\@starttoc 815, 858, 864
\@svsec 274, 278, 288, 299, 321
\@svsechd 318, 354
\@tabarray 1464
\@tempa 1321, 1328
\@tempskipa . . . 256, 258, 259, 266, 295, 296, 339, 340, 343, 358, 359
\@terms 1259, 1262, 1281, 1311
\@thefnmark 926
\@thmcounter 739
\@title 464, 1224
\@tmpnf 1159–1161, 1167, 1180
\@tmpnfx 1166, 1170, 1174
\@tocrmarg 808
\@toodeep 547, 562
\@topnum 414, 1210, 1344
\@topsep 386, 388
\@topsepadd 369, 376, 386
\@trivlist 368
\@twosidetrue 56
\@ucheadfalse 225
\@ucheadtrue . . 230, 234

\@unexpandable@protect 1324
\@unused 1168
\@width 24, 425, 921, 1032, 1039, 1358
\@withappendix 412
\@xdefthm 746, 748
\@xproof 705, 721
\@xsect 336, 338
\@ydefthm 746, 752

A

\abovedisplayshortskip 76, 90, 109
\abovedisplayskip 74, 75, 88, 89, 107, 108
\abstract 1285
abstract (environment) 1284
acks (environment) . 1385
\acmtable 1011
acmtable (environment) 1011
\addcontentsline . . 311, 328, 1061, 1123
\address 1195
\affiliation 1196
\and 1203, 1325
\apbf . 410, 411, 444–450
\appendix 458, 479
\appendixhead . 433, 435
\appenheader 413
appenheader (environment) 413
\arraycolsep . 797, 1458
\arrayrulewidth . . . 801
authinfo (environment) 1193

B

\baselineskip . 1031, 1038, 1232, 1239, 1273, 1349
\baselinestretch . . 63
\belowdisplayshortskip 77, 91, 110
\belowdisplayskip 75, 89, 108
\bf 410, 827, 845, 1329, 1621
\bibemph 1513
\bibemphic 1513
\bibemphsc 1513
\bibindent 1634, 1648, 1649
\bibsc 1516, 1521
\bibyear 1509
\biography 1197
\bottomfraction . . . 928
\bottomstuff 1342
bottomstuff (environment) 1342

C

\c@bottomnumber . . . 928
\c@dbltopnumber . . . 928
\c@figure 953
\c@page 787, 1169
\c@paragraph 212
\c@part 212
\c@secnumdepth 273, 312, 329
\c@section 212
\c@subsection 212
\c@subsubsection . . 212
\c@table 1000
\c@tocdepth 808
\c@topnumber 928
\c@totalnumber 928
\caption . . . 1013, 1081
\category 1317
\centerline 944, 951, 1051, 1076
\citation 1617
\cite 1544
\citeA 1546, 1547
\citeANP 1547
\citeauthoryear 1533, 1556, 1558, 1578, 1580
\citeN 1554
\citeNP 1545
\citeyear . . 1552, 1553
\citeyearNP 1553
\clearpage . . . 456, 911
\clubpenalty 200, 351, 361, 886
\columnsep . . . 160, 898
\columnseprule 161, 897
\copyright 474
\csname 281, 289, 310, 313, 327, 330, 551, 566, 737, 739, 749, 760, 951, 990, 991, 998, 999, 1061, 1062, 1067, 1123, 1124, 1133, 1159, 1628
\CurrentOption 42

D

\dblfloatpagefraction 928
\dblfloatsep 173
\dbltextfloatsep . . 175
\dbltopfraction . . . 928
\describe 655
describe (environment) 655
\description 643
description (environment) 643
\displaystyle 1468, 1483–1485
\do 1612
\doublerulesep 802
\ds@draft 58
\ds@faircopy 48
\ds@preprint 48
\ds@twocolumn 48

E

\edef 278, 550, 565, 1159, 1160, 1166, 1167, 1321, 1480, 1533, 1615
\emph 1514, 1515
\endabstract 1292
\endacmtable 1025
\endappenheader . . . 431
\endarray 1467
\endbottomstuff 1364, 1366
\endcsname 281, 289, 310, 313, 327, 330, 551, 566, 737, 739, 749, 760,

951, 990, 991, 998, 999, 1061, 1062, 1067, 1123, 1124, 1133, 1159, 1628
\enddescribe 665
\enddescription . . . 654
\endenumerate 558
\endfigure . . 991, 1102
\enditemize 596
\endlongenum 575
\endlongitem 607
\endmarray 1467
\endnarrowfig 1093
\endprogram 676
\endproof 708
\endquotation 633
\endquote 642
\endtabbing 676
\endtable 999
\endthebibliography 891
\endtheindex 907
\endtitlepage 790
\endverse 621
\enlargethispage . 1349
\enskip . . . 682, 693, 695, 760, 762, 774
\enumerate 545
enumerate (environment) 545
environments:
abstract 34
acks 36
acmtable 27
appenheader 12
authinfo 32
bottomstuff 35
describe 18
description 17
enumerate 15
figure* 27
figure 26
itemize 16
longenum 15
longitem 16
marray 38
narrowfig 29
program 18
proof 19
quotation 17
quote 17
received 36
sponsor 32
table* 27
table 27
thebibliography 23, 44
theindex 24
titlepage 21
verse 16
\errmessage . 1567, 1591
\evensidemargin . . . 149
\ext@figure 953
\ext@table 1000

F

\f@size 668
\fboxrule 806
\fboxsep 806
\figfilename 960
\figure 990, 1087
figure (environment) 962
figure* (environment) 990
\figurename 953
\firstfoot 1424
\floatpagefraction . 928
\floatsep 166, 167
\fnum@figure 953, 974, 1150
\fnum@table . 1000, 1076
\footheight 155
\footins 164, 805
\footnoterule 919
\footnotesep 163
\footnotesize 99, 419, 871, 951, 965, 984, 994, 1076, 1150, 1238, 1288, 1353, 1387, 1391, 1639
\footskip 156
\fps@figure . . 953, 1083
\fps@table . 1000, 1015
\ftype@figure 953
\ftype@table 1000

G

\G@refundefinedtrue 1622

H

\hb@xt@ 29, 831, 849, 1026, 1094
\headheight 153
\headsep 154
\ht 1127, 1142
\Huge 118
\huge 118
\hyphenpenalty . . . 1223

I

\if 1170, 1174, 1330, 1331, 1334, 1511
\if@faircopy 31, 962, 1495
\if@filesw 1616
\if@inlabel 381
\if@newlist . . . 395, 405
\if@nfeven . . . 1007, 1095, 1116, 1118, 1149, 1151, 1166, 1189
\if@nobreak 262
\if@noskipsec 250, 349, 370
\if@qeded 701, 709
\if@restonecol 791, 892, 908
\if@twocolumn . 780, 896
\if@uchead 224, 302, 322
\ifodd 1161, 1169
\ifvoid 1243
\ignorespaces 366, 428, 719, 724, 750, 767, 1062, 1067, 1124, 1133, 1261, 1267, 1289, 1362, 1510
\immediate 1617
\indexspace 914
\interlinepenalty . 301
\intextsep 169
\it 242, 246, 448, 451, 650, 683, 699, 758, 759, 774, 1335
\item . 444, 446, 448, 449, 451, 618, 630, 639, 679,

687, 714, 723, 754, 771, 904, 1289
\itemindent 572, 602, 603, 613, 614, 626, 648, 649, 1649, 1650
\itemize 588
itemize (environment) 588
\itemsep . . . 96, 115, 508, 520, 528, 880
\ixpt 82

K

\keywords 1314

L

\l@figure 856, 867
\l@part 817
\l@section 837
\l@subsection 853
\l@subsubsection . . 853
\l@table 862
\label . 1165, 1272, 1395
\labelenumi 577
\labelenumii 579
\labelenumiii 582
\labelenumiv 585
\labelsep 488, 491, 494, 503, 517, 525, 533, 538, 543, 589, 592, 603, 649, 660, 681, 689, 716, 723, 756, 773, 803, 877, 1647
\labelwidth . . . 502, 503, 516, 517, 524, 525, 532, 533, 537, 538, 542, 543, 568, 591, 592, 600, 646, 658, 659, 875, 876, 1645, 1646
\LARGE 118, 1221
\Large . . 118, 1405, 1413
\large 118, 826
\lastskip 139
\leftmargin . 93, 112, 500, 505, 515, 523, 531, 536, 541, 572, 590, 591, 601, 612, 615, 616, 624, 627, 636, 637, 647, 659, 660, 876, 877, 1646–1648
\leftmargini 93, 112, 490, 491, 500, 502, 505
\leftmarginii 493, 494, 496–499, 515, 516
\leftmarginiii 496, 523, 524
\leftmarginiv 497, 531, 532
\leftmarginv 498, 536, 537
\leftmarginvi 499, 541, 542
\leftskip 389
\lineskip 61, 1216
\linethickness 731
\listoffigures 856
\listoftables 862
\listparindent 614, 625, 626, 645, 657, 1650
\LoadClass 46
\longenum 560
longenum (environment) 559
\longitem 598
longitem (environment) 597

M

\makelabel 553, 650, 661
\maketitle . . . 1203, 1295, 1299, 1305
\marginparpush 191
\marginparsep 151
\marginparwidth . . . 150
\marray 1457
marray (environment) 1457
\mbox 439
\medskip 1240
\MessageBreak 1298

N

\name 1194
\narrowfig 1079
narrowfig (environment) 1079
\newblock . . . 883, 1654
\newbox . 1008, 1009, 1190, 1191, 1284
\newdef 736
\newfont 411, 420
\newif 31, 224, 701, 893, 1010, 1192
\newline 1194–1197, 1200, 1202
\nocaption 947, 1014, 1082
\noexpand 280, 1169–1177, 1323
\normallineskip . . . 62
\normalsize . 66, 146, 230, 234, 238, 242, 246, 667, 965, 966, 984, 985, 994, 995, 1228

O

\oddsidemargin 148
\onecolumn 782, 909, 1493
\overfullrule 58

P

\p@enumii 581
\p@enumiii . . . 584, 587
\p@enumiv 587
\PackageError 1564, 1586
\PackageWarning . . . 1186, 1244, 1297
\PackageWarningNoLine 40
\pagenumbering 457, 1491
\pageref 1432
\pages 1424
\par@deathcycles 393, 396, 397
\paragraph 244
\parbox 1201
\parindent 195, 197, 241, 245, 352, 421, 464, 466, 572, 602, 645,

648, 657, 680, 688, 715, 723, 755, 822, 842, 902, 925, 1219, 1354, 1393, 1497
\parsep 95, 114, 506, 519, 520, 527, 528, 628, 879, 880, 1651
\parskip 193, 388, 407, 772, 903
\part 228, 481
\partmark 1420
\partopsep . . . 199, 376
\PassOptionsToClass 42
\permission . . 473, 1372
\program 666
program (environment) 666
\proof 703
proof (environment) . 703
\protected@edef . . . 288
\ProvidesPackage . 1503
\ps@myheadings 1399, 1489
\ps@titlepage 1433

Q

\qed 709, 726
\quad . 940, 942, 1047, 1049, 1111, 1113, 1510, 1511
\quotation 622
quotation (environment) 622
\quote 634
quote (environment) . 634

R

received (environment) 1389
\refname 873, 1637, 1641, 1642
\renewenvironment 964, 983, 993
\reserved@a . . . 1557, 1560, 1579, 1582
\reserved@b . . . 1559, 1560, 1581, 1582
\rm 142, 280, 412, 671, 1255
\rom 137, 145, 577, 579, 581, 582, 584, 585, 587, 763, 774
\romannumeral . 550, 565
\rule 427, 1242, 1275, 1361
\runningfoot 1424

S

\savebox 691, 758
\sc 420, 453, 460, 682, 691, 692, 717, 723, 1521
\scriptsize 118
\section 232, 436, 814, 857, 863, 899, 1640
\sectionmark 1421
\sf 230, 234, 238, 464, 466, 873, 1224, 1229, 1233, 1387, 1403, 1411
\shortcite . 1548, 1549
\shortciteA . 1550, 1551
\shortciteANP 1551
\shortciteN 1576
\shortciteNP 1549
\skip@ 139, 141
\small 80, 410, 453, 669, 1403, 1411
sponsor (environment) 1199
\start@cite . . . 1532, 1544, 1546, 1548, 1550, 1552
\string . 1299, 1305, 1564, 1568, 1587, 1592, 1617
\strut 1200, 1368
\subitem 914
\subsection 236
\subsectionmark . . 1422
\subsubitem 914
\subsubsection 240
\suppressfloats 416, 1212, 1350

T

\tabbing 673
\tabbingsep 803
\tabcolsep 800
\table 998, 1019
table (environment) . 992
table* (environment) 998
\tablename 1000
\tableofcontents . . 813
\terms 1311
\textfloatsep 167, 423, 1356
\textfraction 928
\textheight 158, 415, 970, 1345
\textsc 1516
\textup . . 145, 289, 1256
\textwidth 159, 1026, 1094, 1128, 1143, 1242, 1275
\thebibliography 869, 1638
thebibliography (environment) 869, 1638
\theenumi . 578, 581, 584
\theenumii . . . 580, 584
\theenumiii . . . 583, 587
\theenumiv 586
\theequation 777
\thefigure 953, 1158, 1159, 1165, 1171, 1175
\theindex 894
theindex (environment) 894
\thepage 1183, 1186, 1407, 1411, 1625
\theparagraph 218
\thepart 218
\thesection 218, 485, 486
\thesubsection 218, 486
\thesubsubsection . 218
\thetable 1000
\thispagestyle 786, 901, 1209
\thr@@ 1537
\tiny . 118, 439, 1409, 1419, 1436, 1438
\titlepage 778
titlepage (environment) 778
\today 1440
\topfraction 928
\topmargin 152

\topsep 94, 113, 369, 507, 518, 526, 878
\tt 976
\twocolumn . . . 792, 899

U

\unitlength 730
\unskip 140, 357, 378, 727, 1255, 1256, 1510
\unvbox 972

V

\vbox 464, 466, 970, 1020, 1028, 1064, 1074, 1088, 1127, 1142, 1287
\verse 609
verse (environment) . 609
\vpt 120
\vrule 1032, 1039, 1241, 1274

W

\widowpenalty . 201, 885
\write 1168, 1617

X

\xdef 739, 1326
\xivpt 122
\xpt 68
\xviipt 123
\xxpt 124
\xxvpt 125

Z

\z@skip 389